

PREMIUM ALUMINUM / MADE TO MEASURE

Open up the everyday.

A glass wall when closed.
A wider opening when folded.

Heavy-duty folding glass doors with Low-E double glazing, argon insulation, a PA66 thermal break, and an integrated folding insect screen. The same premium construction, tailored to your project.

CUSTOM DIMENSIONS

Width and height are made to fit your opening. Final measurements are confirmed for your project.

CUSTOM CONFIGURATIONS

Choose the panel arrangement, stacking side, opening direction, and daily-access options for your selected system.

PREMIUM CONSTRUCTION

Thermally broken aluminum, multi-point locking, weather seals, a low-profile track, and a folding screen.



Featured system shown. Your dimensions and panel layout are customized.

PLAN YOUR QUOTE

Opening width and height
Preferred panel configuration and finish
Delivery city and postal code
Target project timing

CONFIRM BEFORE ORDERING

Final measurements and specifications
Availability and delivery costs
Installation scope and schedule
Written warranty and return terms

Ask us about custom sizes, supply, delivery, and professional installation.

SUPPLY + DELIVERY + INSTALLATION / CONNECTICUT & NEW YORK

(646) 300-2430 | (718) 607-5748 | mvvconstructioncorp@gmail.com

80-SERIES / CONSTRUCTION & SPECIFICATIONS

The complete system.

Technical details for the featured folding-door system. Dimensions, configuration, finish, and included accessories are confirmed for your custom order.

FEATURE	FEATURED SYSTEM / CUSTOM ORDER
System series	80-Series Architectural Folding Glass Door
Custom dimensions	Width and height tailored to your project. Final frame and opening dimensions confirmed after measurement.
Custom configurations	Panel count, folding arrangement, stacking side, opening direction, and daily-access options customized to the selected system.
Frame material	Architectural-grade 6063-T6 aluminum; 2.0 mm profile thickness for the featured system.
Thermal break	High-performance PA66 nylon thermal barrier.
Glass technology	Double-glazed Low-E tempered glass with argon insulation; 5 mm glass listed for the featured package. Confirm selected glazing.
Frame thickness	65 mm as listed for the featured package; confirm the profile for your selected system.
Finish	Premium powder-coated matte black. White and other custom finishes available depending on the selected system.
Security & handle	Key-operated multi-point steel locking system with interior handle and key access.
Bottom track	Low-profile weatherproof track with integrated drainage.
Seals & safety	Interlocking male/female side and bottom weather seals, designed for finger-pinch protection and tight sealing.
Insect protection	Integrated retractable nylon folding fly screen included in the featured package.
Hardware	Folding panel connectors, hinges, guide components, and precision rollers.
Services	Direct supply, jobsite delivery, and professional local installation in Connecticut and New York. Scope itemized in your quote.

Custom sizing does not replace a site measurement or approved shop drawing. Confirm final fit, handling, available options, and installation requirements with our team before ordering.